Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-419-8696

| Cross Sectional Shape: |
|---|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| Between 0.242 inches and 0.273 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| Between 0.594 inches and 0.656 inches |
| Minimum Inside Bending Radius: |
| 4.000 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Plain 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Burst Test Pressure: |
| 11000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer molded rubber, synthetic and 1st layer braided wire |
| Maximum Operating Pressure: |
| 2750.0 pounds per square inch |
| Thread Size: |
| 0.250 inches 1st end |
| Hydrostatic Test Pressure: |
| 5500.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Oil resistant and weatherproof |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 122.000 inches |
| Media For Which Designed: |
| Hydraulic fluid, water base and fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| N/a |

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0