## NSN 4720-00-421-3802

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-421-3802

Cross Sectional Shape: Round Thread Direction: Right-hand 1st end Inside Diameter: Between 0.735 inches and 0.781 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: Between 1.156 inches and 1.219 inches							
Thread Direction: Right-hand 1st end Inside Diameter: Between 0.735 inches and 0.781 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter:							
Right-hand 1st end Inside Diameter: Between 0.735 inches and 0.781 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter:							
Inside Diameter: Between 0.735 inches and 0.781 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter:							
Between 0.735 inches and 0.781 inches  Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response  Outside Diameter:							
Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter:							
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response  Outside Diameter:							
Outside Diameter:							
Between 1.156 inches and 1.219 inches							
Minimum Inside Bending Radius:							
9.500 inches							
Exterior Color:							
Black							
Connection Style:							
Plain 1st end							
End Connection Design:							
Straight 1st end							
Connection Type:							
Threaded external pipe 1st end							
Burst Test Pressure:							
5000.0 pounds per square inch							
Layer Composition And Location:							
Outer layer molded rubber, synthetic and 1st layer braided wire							
Maximum Operating Pressure:							
1250.0 pounds per square inch							
Thread Size:							
0.750 inches 1st end							
Hydrostatic Test Pressure:							
2500.0 pounds per square inch							
Outer Covering Environmental Protection:							
Oil resistant and weatherproof							
Inside Surface Condition:							
Smooth							
Measuring Method And Length:							
37.000 inches							
Media For Which Designed:							
Fuel/oil, hydrocarbon and hydraulic fluid, water base single response							
Thread Series Designator:							
Npt 1st end							
Shelf Life:							
N/a							

## NSN 4720-00-421-3802

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0