## NSN 4720-00-421-3807

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-421-3807

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Outside Diameter:
0.594 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided cotton cord
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant and fuel resistant and oil resistant
Inside Surface Condition:

Smooth

## NSN 4720-00-421-3807

Nonmetallic Hose Assembly - Page 2 of 2



## Measuring Method And Length: 12.375 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization: No

**Fiig:** A542a0