## NSN 4720-00-421-3886

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-421-3886

Cross Sectional Shape:
Round
Thread Class:
3b and 2a 2nd end
Thread Direction:
Right-hand 2nd end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.562 inches
Connection Style:
Inverted flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Unthreaded external tube 1st end
Thready Qty Per Inch (tpi):
18 2nd end
Burst Test Pressure:
4500.0 pounds per square inch
Layer Composition And Location:
2nd layer rubber impregnated braided cotton cord and 1st layer rubber impregnated braided cotton cord and outer layer molded rubber,
chloroprene
Thread Size:
0.500 inches and 0.688 inches 2nd end
Seat Angle:
42.0 degrees 2nd end
Outer Covering Environmental Protection:
Cold resistant and oil resistant and corrosion resistant and waterproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
25.000 inches excluding end fittings
Outside Diameter Tube Accommodated:
0.656 inches 1st end
Special Features:
Second end has banjo fitting, 0.656 in. Id
Thread Series Designator:
Unf and uns 2nd end

N/a

Shelf Life:

## NSN 4720-00-421-3886

Nonmetallic Hose Assembly - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A542a0