Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-421-6498

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.595 inches
Minimum Inside Bending Radius:
4.500 inches
Inner Conveying Tube Material:
Plastic, ethylene propylene dienne-ply-methylene
Exterior Color:
Green
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Fitting Component And Surface Treatment:
Complete fitting passivate 1st end
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
10000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer cover, plastic, ethylene proplylene dienne-poly-methylene
Maximum Operating Pressure:
2500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
~

Nonmetallic Hose Assembly - Page 2 of 2



### Hydrostatic Test Pressure:

5000.0 pounds per square inch

# Inside Surface Condition:

Smooth

# Measuring Method And Length:

26.703 inches

## **Special Features:**

Inner conveying tube material-lastic, ethylene propylene dienne-ply-methylene

## Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A542a0