## NSN 4720-00-422-2177

33.000 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-422-2177

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 3a 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.422 inches   |
| Tempurature Rating:  |
| -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response  |
| Outside Diameter:  |
| 0.815 inches   |
| Minimum Inside Bending Radius:   |
| 8.000 inches   |
| Exterior Color:  |
| Natural  |
| Connection Style:  |
| External seat for gasket seal (boss) 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded external boss 1st end   |
| Thready Qty Per Inch (tpi):  |
| 12 1st end   |
| Burst Test Pressure:   |
| 22000.0 pounds per square inch   |
| Layer Composition And Location:  |
| 2nd layer spirally wrapped corrosion resistant steel fabric and 1st layer braided corrosion resistant steel wire and outer layer braided |
| corrosion resistant steel wire   |
| Maximum Operating Pressure:  |
| 5000.0 pounds per square inch  |
| Thread Size:   |
| 1.750 inches 1st end   |
| Hydrostatic Test Pressure:   |
| 11000.0 pounds per square inch   |
| Outer Covering Environmental Protection:   |
| Corrosion resistant  |
| Criticality Code Justification:  |
| Zzzy   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |

## NSN 4720-00-422-2177

**Fiig:** A542a0

Nonmetallic Hose Assembly - Page 2 of 2



| Special Features:  |
|--|
| Packaged in a heat sealed polyethylene tube  |
| Thread Series Designator:  |
| Un 1st end   |
| Reference Number Differentiating Characteristics:  |
| Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |