## NSN 4720-00-423-0049



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-423-0049 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.790 inches **Minimum Inside Bending Radius:** 6.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Perforated outer cover **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided fiber and 1st layer braided fiber and outer layer molded polyurethane **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:** 4000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 

33.000 inches

**Thread Series Designator:** 

Unf 1st end

## NSN 4720-00-423-0049

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0