## NSN 4720-00-423-3089



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-423-3089 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** Between 0.594 inches and 0.658 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.375 inches **Minimum Inside Bending Radius:** 3.000 inches

**Connection Style:** 

Swivel nut flare 1st end

**End Connection Design:** Straight 1st end

**Connection Type:** 

Threaded internal tube 1st end

**Burst Test Pressure:** 

1600.0 pounds per square inch

**Layer Composition And Location:** 

Outer layer molded rubber, synthetic and 1st layer braided textile yarn

**Maximum Operating Pressure:** 

400.0 pounds per square inch

**Thread Size:** 

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

**Hydrostatic Test Pressure:** 

800.0 pounds per square inch

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

8.750 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

## NSN 4720-00-423-3089

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0