NSN 4720-00-423-3713

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-423-3713 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.750 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 1.086 inches **Minimum Inside Bending Radius:** 9.500 inches **Connection Style:** Swivel nut with compression sleeve 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 18 2nd end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, chloroprene and 1st layer braided steel wire **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 4500.0 pounds per square inch **Outer Covering Environmental Protection:** Ozone resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 52.250 inches

Media For Which Designed:

Hydraulic fluid single response

NSN 4720-00-423-3713

Nonmetallic Hose Assembly - Page 2 of 2



Thread S	eries	Designa	ator
Un 1st en	d		

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0