NSN 4720-00-430-9705

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-430-9705		
Cross Sectional Shape:		
Round		
Thread Class:		
3b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.188 inches		
Tempurature Rating:		
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response		
Outside Diameter:		
0.250 inches		
Minimum Inside Bending Radius:		
2.000 inches		
Exterior Color:		
Natural		
End Connection Design:		
Straight 1st end		
Connection Type:		
Threaded internal tube 1st end		
Features Provided:		
Electrostatic discharge capability		
Burst Test Pressure:		
12000.0 pounds per square inch		
Layer Composition And Location:		
Outer layer braided corrosion resistant steel wire		
Maximum Operating Pressure:		
1500.0 pounds per square inch		
Thread Size:		
0.438 inches 1st end		
Seat Angle:		
37.0 degrees 1st end		
Hydrostatic Test Pressure:		
3000.0 pounds per square inch		
Outer Covering Environmental Protection:		
Corrosion resistant		

Vacuum In Torr:

Inside Surface Condition:

Smooth

50.8

Measuring Method And Length:

10.500 inches working

NSN 4720-00-430-9705

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator
Unif 1st	end	

Specification Data:

96906-ms8000 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0