Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-431-9427

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
4500.0 pounds per square inch
Layer Composition And Location:
2nd layer braided textile yarn and 1st layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
11250.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
2250.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
13.250 inches
Media For Which Designed:
Hydraulic fluid, water base single response
Thread Series Designator:
Nptf 1st end
Shelf Life:
N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0