

View Online at <https://aerobasegroup.com/nsn/4720-00-432-1267>

**Cross Sectional Shape:**

Round

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.310 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Outside Diameter:**

0.610 inches

**Minimum Inside Bending Radius:**

2.000 inches

**Exterior Color:**

Black

**Connection Style:**

Swivel nut, inverted flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external tube 1st end

**Features Provided:**

Reusable end fittings

**Burst Test Pressure:**

1000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer rubber impregnated braided fabric and 1st layer braided corrosion resistant steel wire, partial coverage

**Maximum Operating Pressure:**

250.0 pounds per square inch

**Thread Size:**

0.625 inches 1st end

**Seat Angle:**

45.0 degrees 1st end

**Hydrostatic Test Pressure:**

500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

12.000 inches

**Media For Which Designed:**

Air and fuel/oil, hydrocarbon and water single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0