## NSN 4720-00-432-2483

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-432-2483

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.312 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Natural
Angle Between Rigid Elbow Fittings In Deg:
180.0
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Threaded internal tube 1st end
Threaded internal tube 1st end  Features Provided:
Threaded internal tube 1st end  Features Provided:  Reusable end fittings
Threaded internal tube 1st end  Features Provided:  Reusable end fittings  Burst Test Pressure:
Threaded internal tube 1st end  Features Provided: Reusable end fittings  Burst Test Pressure: 12000.0 pounds per square inch
Threaded internal tube 1st end  Features Provided: Reusable end fittings  Burst Test Pressure: 12000.0 pounds per square inch  Layer Composition And Location:
Threaded internal tube 1st end  Features Provided: Reusable end fittings  Burst Test Pressure: 12000.0 pounds per square inch  Layer Composition And Location: Outer layer braided corrosion resistant steel wire
Threaded internal tube 1st end  Features Provided: Reusable end fittings  Burst Test Pressure: 12000.0 pounds per square inch  Layer Composition And Location: Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:
Threaded internal tube 1st end  Features Provided: Reusable end fittings  Burst Test Pressure: 12000.0 pounds per square inch  Layer Composition And Location: Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure: 1500.0 pounds per square inch
Threaded internal tube 1st end  Features Provided: Reusable end fittings Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size:
Threaded internal tube 1st end  Features Provided: Reusable end fittings Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end
Threaded internal tube 1st end  Features Provided: Reusable end fittings Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure: 1500.0 pounds per square inch  Thread Size: 0.438 inches 1st end  Seat Angle:
Threaded internal tube 1st end  Features Provided: Reusable end fittings  Burst Test Pressure: 12000.0 pounds per square inch  Layer Composition And Location: Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure: 1500.0 pounds per square inch  Thread Size: 0.438 inches 1st end  Seat Angle: 37.0 degrees 1st end
Threaded internal tube 1st end  Features Provided: Reusable end fittings  Burst Test Pressure: 12000.0 pounds per square inch  Layer Composition And Location: Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure: 1500.0 pounds per square inch  Thread Size: 0.438 inches 1st end  Seat Angle: 37.0 degrees 1st end  Hydrostatic Test Pressure:
Threaded internal tube 1st end  Features Provided: Reusable end fittings  Burst Test Pressure: 12000.0 pounds per square inch  Layer Composition And Location: Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure: 1500.0 pounds per square inch  Thread Size: 0.438 inches 1st end  Seat Angle: 37.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch
Threaded internal tube 1st end  Features Provided: Reusable end fittings  Burst Test Pressure: 12000.0 pounds per square inch  Layer Composition And Location: Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure: 1500.0 pounds per square inch  Thread Size: 0.438 inches 1st end  Seat Angle: 37.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Flow Angle:

## NSN 4720-00-432-2483

Nonmetallic Hose Assembly - Page 2 of 2



Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
9.000 inches working
Thread Series Designator:
Unf 1st end
Specification Data:
73342-6849471-041090 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0