## NSN 4720-00-432-2836

**Cross Sectional Shape:** 

Corrosion resistant

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-432-2836

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
2.000 inches
Angle Between Rigid Elbow Fittings In Deg:
255.0
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
20 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
45.0 degrees 1st end
Outer Covering Environmental Protection:

## NSN 4720-00-432-2836

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
4.875 inches working and 5.125 inches working
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0