## NSN 4720-00-432-7286

**Cross Sectional Shape:** 

Round

Thread Class: 2b 2nd end

**Thread Direction:** 

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-432-7286

Right-hand 1st end					
Inside Diameter:					
0.250 inches					
Tempurature Rating:					
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response					
Outside Diameter:					
0.568 inches					
Inner Conveying Tube Style:					
Annular close-pitch corrugated					
Exterior Color:					
Natural					
Connection Style:					
Swivel nut, inverted flare 2nd end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 2nd end					
Burst Test Pressure:					
2000.0 pounds per square inch					
Layer Composition And Location:					
Outer layer braided corrosion resistant steel wire					
Maximum Operating Pressure:					
500.0 pounds per square inch					
Thread Size:					
0.625 inches 1st end					
Seat Angle:					
12.0 degrees 2nd end					
Hydrostatic Test Pressure:					
1000.0 pounds per square inch					
Flow Angle:					
90.0 degrees 2nd end					
Outer Covering Environmental Protection:					
Corrosion resistant					
Measuring Method And Length:					
34.000 inches					
Special Features:					

Both ends have self sealing connections

## NSN 4720-00-432-7286

Metallic Hose Assembly - Page 2 of 2



		•		
I hi	hear	Series	I Jaciu	nator:
	Cau	061163	Desid	nator.

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0