## NSN 4720-00-432-9608

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-432-9608

Cross Sectional Chance
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.423 inches
Minimum Inside Bending Radius:
3.500 inches
Exterior Color:
Black
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided polyester cord and 1st layer braided polyester cord and outer layer molded polyurethane
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Hydraulic solution resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
60.000 inches
Special Features:
Permanently attached fittings
Thread Series Designator:
Npt 1st end
Shelf Life:

## NSN 4720-00-432-9608

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0