

View Online at <https://aerobasegroup.com/nsn/4720-00-434-1260>

Cross Sectional Shape:

Round

Inside Diameter:

1.500 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

Flange Thickness:

0.368 inches 1st end

Outside Diameter:

1.718 inches

Minimum Inside Bending Radius:

9.000 inches

Exterior Color:

Natural

Angle Between Rigid Elbow Fittings In Deg:

180.0

Center To Center Distance Between Bolt Holes Along Width:

1.795 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

1.800 inches 1st end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.400 inches 1st end

Flange Width:

2.395 inches 1st end

Connection Style:

Plain swivel w/ gasket groove 2nd end

Bolt Hole Diameter:

0.272 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Plain face flange 2nd end

Features Provided:

Reusable end fittings

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

250.0 pounds per square inch

Hydrostatic Test Pressure:

800.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

33.750 inches

Flange Style:

Rectangular (includes square) 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0