## NSN 4720-00-435-4255

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-435-4255

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 2.950 inches   |
| Tempurature Rating:  |
| -65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response  |
| Outside Diameter:  |
| 3.335 inches   |
| Minimum Inside Bending Radius:   |
| 15.000 inches  |
| Exterior Color:  |
| Natural  |
| Connection Style:  |
| Plain optional end 2nd end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal pipe 2nd end   |
| Layer Composition And Location:  |
| Outer layer polytetrafluoroethylene impregnated glass fiber and 1st layer braided corrosion resistant steel wire |
| Maximum Operating Pressure:  |
| 100.0 pounds per square inch   |
| Thread Size:   |
| 3.000 inches 2nd end   |
| Hydrostatic Test Pressure:   |
| 200.0 pounds per square inch   |
| Flow Angle:  |
| 90.0 degrees 2nd end   |
| Inside Surface Condition:  |
| Convoluted   |
| Measuring Method And Length:   |
| 57.250 inches  |
| Thread Series Designator:  |
| Npt 1st end  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |

No

## NSN 4720-00-435-4255

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0