Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-435-4276

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
1.813 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response	
Outside Diameter:	
2.219 inches	
Minimum Inside Bending Radius:	
13.250 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
12 1st end	
Burst Test Pressure:	
1400.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord	
Maximum Operating Pressure:	
350.0 pounds per square inch	
Thread Size:	
2.500 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
65.000 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Un 1st end	
Shelf Life:	
N/a	

NSN 4720-00-435-4276

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0