Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-435-5641

Cross Section	
Cross Sectiona Round	al Snape:
Thread Class:	
3b 1st end	
Thread Direction	
Right-hand 1st	
Inside Diamete	
0.156 inches	
Tempurature R	-
	ahrenheit and 300.0 degrees fahrenheit single response
Outside Diame	eter:
0.375 inches	
	le Bending Radius:
1.750 inches	
Connection St	
Swivel nut, flar	
End Connectio	-
Straight 1st end	
Connection Ty	
Threaded interr	
Thready Qty P	er Inch (tpi):
24 1st end	
Burst Test Pre	ssure:
6000.0 pounds	per square inch
Layer Compos	ition And Location:
Outer layer brai	ded corrosion resistant steel wire, partial coverage and 1st layer braided corrosion resistant steel wire
Maximum Ope	rating Pressure:
1000.0 pounds	per square inch
Thread Size:	
0.375 inches 1s	st end
Seat Angle:	
12.0 degrees 1s	st end
Hydrostatic Te	est Pressure:
3000.0 pounds	per square inch
Outer Covering	g Environmental Protection:
Corrosion resist	tant
Inside Surface	Condition:
Smooth	
Measuring Me	thod And Length:
297.000 inches	working and 303.000 inches working
Thread Series	Designator:
Unjf 1st end	

## NSN 4720-00-435-5641

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

