

View Online at <https://aerobasegroup.com/nsn/4720-00-436-2984>

Cross Sectional Shape:

Round

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.359 inches and 0.391 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.734 inches and 0.766 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Black or natural

Connection Style:

Swivel nut, inverted flare 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded external tube 2nd end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided rayon cord and 1st layer braided rayon cord and outer layer molded rubber, synthetic

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

0.625 inches 1st end

Seat Angle:

45.0 degrees 2nd end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

32.000 inches and 33.500 inches

Media For Which Designed:

Hydraulic fluid and fuel/oil, hydrocarbon single response

Special Test Features:

1st end connection design, prebent tube 9.500 in.Lg./2nd end connection design, prebent tube 10.500 in.Lg

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0