

View Online at <https://aerobasegroup.com/nsn/4720-00-436-2986>

Cross Sectional Shape:

Round

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.750 inches

Minimum Inside Bending Radius:

4.000 inches

Connection Style:

Swivel nut, inverted flare 1st end

Connection Type:

Threaded external tube 1st end

Burst Test Pressure:

4500.0 pounds per square inch

Layer Composition And Location:

2nd layer braided textile yarn and 1st layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

1125.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2250.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and ozone resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

29.000 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Special Test Features:

1st end connection design, prebenttube

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0