## NSN 4720-00-436-6393

W/polytetrafluoroethylene external support

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-436-6393

Cross Sectional Shape:		
Round		
Thread Class:		
3b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.219 inches		
Tempurature Rating:		
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response		
Outside Diameter:		
0.390 inches		
Minimum Inside Bending Radius:		
1.500 inches		
Connection Style:		
Swivel nut, flareless 1st end		
End Connection Design:		
Straight 1st end		
Connection Type:		
Threaded internal tube 1st end		
Features Provided:		
Electrostatic discharge capability		
Burst Test Pressure:		
16000.0 pounds per square inch		
Layer Composition And Location:		
Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire		
Maximum Operating Pressure:		
3000.0 pounds per square inch		
Thread Size:		
0.438 inches 1st end		
Seat Angle:		
12.0 degrees 1st end		
Hydrostatic Test Pressure:		
6000.0 pounds per square inch		
Outer Covering Environmental Protection:		
Heat resistant		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		
17.625 inches		
Special Features:		

## NSN 4720-00-436-6393

Nonmetallic Hose Assembly - Page 2 of 2



		_
Thread	l Series	Designator:

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0