## NSN 4720-00-437-0244

Smooth

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-437-0244

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
Between 1.125 inches and 1.187 inches
Minimum Inside Bending Radius:
5.500 inches
Exterior Color:
Natural
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
2500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire
Maximum Operating Pressure:
750.0 pounds per square inch
Thread Size:
1.312 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
1500.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Vacuum In Torr:
203.2
Inside Surface Condition:

## NSN 4720-00-437-0244

Nonmetallic Hose Assembly - Page 2 of 2



## Measuring Method And Length: 50.000 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unj 2nd end Specification Data: 96906-ms87028 government standard Shelf Life: N/a Unit Of Measure:

No

Fiig:

A542a0

Demilitarization: