

View Online at <https://aerobasegroup.com/nsn/4720-00-437-1135>

Cross Sectional Shape:

Round

Inside Diameter:

Between 0.305 inches and 0.336 inches

Temperature Rating:

-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

Between 0.547 inches and 0.637 inches

Minimum Inside Bending Radius:

2.800 inches

Connection Style:

Swivel nut with loose or integral clinch sleeve 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

4000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and 1st layer braided cotton cord and outer layer rubber impregnated braided fabric

Maximum Operating Pressure:

1000.0 pounds per square inch

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant and oil resistant and fuel resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

12.800 inches and 13.300 inches

Media For Which Designed:

Hydraulic fluid single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0