Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-437-4793

^ -	na Castianal Chana
	oss Sectional Shape:
	read Class:
	1st end
	read Direction:
	ght-hand 1st end
	side Diameter:
-	88 inches
	mpurature Rating:
	5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
	Itside Diameter:
	12 inches
	nimum Inside Bending Radius:
-	100 inches
	nnection Style:
	vivel nut flare 1st end
	d Connection Design:
	aight 1st end
	nnection Type:
	readed internal tube 1st end
	atures Provided:
	ectrostatic discharge capability
	rst Test Pressure:
12	000.0 pounds per square inch
La	yer Composition And Location:
Ou	ter layer braided corrosion resistant steel wire
Ма	ximum Operating Pressure:
15	00.0 pounds per square inch
Th	read Size:
0.4	38 inches 1st end
Se	at Angle:
37.	0 degrees 1st end
Hy	drostatic Test Pressure:
30	00.0 pounds per square inch
Ou	ter Covering Environmental Protection:
Co	Id resistant and corrosion resistant
Va	cuum In Torr:
50	8
Ins	ide Surface Condition:
Sm	nooth
Ме	easuring Method And Length:
12	.000 inches working

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms8005 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0