## NSN 4720-00-441-2167

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-441-2167
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.562 inches
Minimum Inside Bending Radius:
4.625 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:

**Hydrostatic Test Pressure:** 

3000.0 pounds per square inch

**Outer Covering Environmental Protection:** 

Corrosion resistant and fuel resistant and oil resistant

Vacuum In Torr:

50.8

**Inside Surface Condition:** 

Smooth

## NSN 4720-00-441-2167

Nonmetallic Hose Assembly - Page 2 of 2



<b>Measuring Method And Length:</b>
64.000 inches working
Special Features:
Permanently attached fittings
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0