Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-442-5735

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.880 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single re	esponse
Outside Diameter:	
1.230 inches	
Minimum Inside Bending Radius:	
7.380 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Reusable end fittings	
Thready Qty Per Inch (tpi):	
12 1st end	
Burst Test Pressure:	
3200.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided wire and 1st layer braided textile yarn and out	ter layer rubber impregnated braided cotton cord
Maximum Operating Pressure:	
800.0 pounds per square inch	
Thread Size:	
1.000 inches 2nd end	
Seat Angle:	
37.0 degrees 1st end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
50.000 inches working	
Media For Which Designed:	
Air and fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Un 1st end	

## NSN 4720-00-442-5735

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

