NSN 4720-00-442-6545

Nonmetallic Hose Assembly - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/4720-00-442-6545
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.340 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
Outside Diameter:
0.590 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
26.750 inches working
Special Features:
Layer compoisition and location 1st layer, cadium plated braided carbon steel wire, 2nd layer molded polytetrafluoroethylene, outer laye
braided corrosion resistant steel wire
Thread Series Designator:
Unf 1st end
Shelf Life:

N/a

NSN 4720-00-442-6545

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0