NSN 4720-00-442-9798

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-442-9798 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.875 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 1.156 inches **Minimum Inside Bending Radius:** 5.500 inches **Exterior Color:** Natural **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end **Burst Test Pressure:** 2500.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire, partial coverage and 1st layer braided corrosion resistant steel wire **Maximum Operating Pressure:**

750.0 pounds per square inch

Thread Size:

1.312 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

1500.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

14.500 inches working

NSN 4720-00-442-9798

Nonmetallic Hose Assembly - Page 2 of 2



M	edia	For	Whic	h D	esian	ed:
w	Cuia		***	,,,	CSIGII	cu.

Alcohol, ethyl and alcohol, methyl and fuel/oil, hydrocarbon and water, fresh single response

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0