Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-444-1734

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.590 inches
Minimum Inside Bending Radius:
4.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded plastic and 1st layer woven polyester fiber cord
Maximum Operating Pressure:
2500.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
5000.0 pounds per square inch
Outer Covering Environmental Protection:
Hydraulic solution resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
102.000 inches
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a

NSN 4720-00-444-1734

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0