NSN 4720-00-445-9747

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-445-9747

Inside Diameter: 0.250 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 2500.0 pounds per square inch Maximum Operating Pressure: 500.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Inside Surface Condition: Smooth
0.250 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 2500.0 pounds per square inch Maximum Operating Pressure: 500.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Inside Surface Condition:
Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 2500.0 pounds per square inch Maximum Operating Pressure: 500.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Inside Surface Condition:
Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 2500.0 pounds per square inch Maximum Operating Pressure: 500.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Inside Surface Condition:
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 2500.0 pounds per square inch Maximum Operating Pressure: 500.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Inside Surface Condition:
Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 2500.0 pounds per square inch Maximum Operating Pressure: 500.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Inside Surface Condition:
Connection Type: Threaded internal tube 1st end Burst Test Pressure: 2500.0 pounds per square inch Maximum Operating Pressure: 500.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Inside Surface Condition:
Threaded internal tube 1st end Burst Test Pressure: 2500.0 pounds per square inch Maximum Operating Pressure: 500.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Inside Surface Condition:
Burst Test Pressure: 2500.0 pounds per square inch Maximum Operating Pressure: 500.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Inside Surface Condition:
2500.0 pounds per square inch Maximum Operating Pressure: 500.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Inside Surface Condition:
Maximum Operating Pressure: 500.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Inside Surface Condition:
500.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Inside Surface Condition:
Flow Angle: 45.0 degrees 2nd end Inside Surface Condition:
45.0 degrees 2nd end Inside Surface Condition:
Inside Surface Condition:
Smooth
Measuring Method And Length:
48.000 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0