## NSN 4720-00-446-3146

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-446-3146

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.375 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit and 212.0 degrees fahrenheit single response                             |
| Outside Diameter:   |
| 0.750 inches  |
| Connection Style:   |
| Inverted flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded external pipe 1st end  |
| Thready Qty Per Inch (tpi):   |
| 14 1st end  |
| Burst Test Pressure:  |
| 900.0 pounds per square inch  |
| Layer Composition And Location:   |
| Outer layer molded rubber, chloroprene  |
| Thread Size:  |
| 0.500 inches 1st end  |
| Seat Angle:   |
| 30.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 450.0 pounds per square inch  |
| Outer Covering Environmental Protection:  |
| Abrasion resistant and mildew resistant and ozone resistant and acid resistant and fuel resistant |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 63.375 inches   |
| Thread Series Designator:   |
| Nptf 1st end  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 4720-00-446-3146

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0