

View Online at <https://aerobasegroup.com/nsn/4720-00-447-0170>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.438 inches

Temperature Rating:

-65.0 degrees fahrenheit and 156.0 degrees fahrenheit single response

Outside Diameter:

0.859 inches

Minimum Inside Bending Radius:

5.750 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

14000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber, chloroprene

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

7000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.500 inches working

Media For Which Designed:

Air and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Specification Data:

96906-ms28759 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0