Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-447-3583

cross Sectional Shape:	
Round	
hread Direction:	
Right-hand 1st end	
nside Diameter:	
.500 inches	
empurature Rating:	
40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
.970 inches	
Iinimum Inside Bending Radius:	
.000 inches	
Exterior Color:	
Black	
Connection Style:	
nverted flare 1st end	
nd Connection Design:	
straight 1st end	
Connection Type:	
hreaded external pipe 1st end	
eatures Provided:	
Reusable end fittings	
Burst Test Pressure:	
4000.0 pounds per square inch	
ayer Composition And Location:	
nd layer braided wire and 1st layer braided wire and outer layer molded rubber	, synthetic
faximum Operating Pressure:	
500.0 pounds per square inch	
hread Size:	
.500 inches 1st end	
eat Angle:	
0.0 degrees 1st end	
lydrostatic Test Pressure:	
000.0 pounds per square inch	
Duter Covering Environmental Protection:	
uel resistant and hydraulic solution resistant and oil resistant	
nside Surface Condition:	
Smooth	
leasuring Method And Length:	
5.500 inches	
ledia For Which Designed:	
uel/oil, hydrocarbon single response	

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

**Thread Series Designator:** 

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0