NSN 4720-00-448-8482

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-448-8482

Cross Sectional Shape:
Round
Inside Diameter:
2.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Outside Diameter:
Between 2.656 inches and 2.781 inches
Hose Or Tubing Specification/std Data:
Mil-h-18288 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Features Provided:
Self-sealing
Burst Test Pressure:
150.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, chloroprene
Maximum Operating Pressure:
45.0 pounds per square inch
Hydrostatic Test Pressure:
75.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and mildew resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
22.250 inches
Special Features:
Inner conveying tube material-rubber, synthetic; nipples drilled for safety wire
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Specification Data:
Mil-h-18288 professional/industrial association specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0

Mil-h-18288 spec.

Mil-std (military Standard):