

View Online at <https://aerobasegroup.com/nsn/4720-00-449-6630>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Left-hand 1st end

Inside Diameter:

0.188 inches

Outside Diameter:

0.531 inches

Exterior Color:

Red

First End Fitting Specification/std Data:

Mil ms15011 standard (includes industry or association standards, individual manufactureer standards, etc.).

Second End Fitting Specification/std Data:

Mil ms15011 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut, compression 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

24 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

600.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, chloroprene

Thread Size:

0.562 inches 1st end

Hydrostatic Test Pressure:

250.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

150.000 inches excluding end fittings

Second End Swivel Action Capability:

Not included

Seat Radius:

0.196 inches 2nd end

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Acetylene single response

Thread Series Designator:

Unf 2nd end

Specification Data:

81348-zz-h-461 government specification

Specification Or Standard:

2 type and a style

Departure From Cited Document:

As modified by thread size and series on 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0