Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-450-6622

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.500 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
0.970 inches	
Minimum Inside Bending Radius:	
7.000 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
14000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber, synthetic	
Maximum Operating Pressure:	
3500.0 pounds per square inch	
Thread Size:	
0.875 inches 2nd end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
7000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
20.750 inches	
Special Features:	
With o ring	
Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.875 inches 2nd end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 20.750 inches Special Features:	



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0