Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-450-6638

oss Sectional Shape:	
bund	
nread Direction:	
ght-hand 1st end	
side Diameter:	
500 inches	
empurature Rating:	
5.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
utside Diameter:	
822 inches	
inimum Inside Bending Radius:	
750 inches	
onnection Style:	
ain 1st end	
nd Connection Design:	
raight 1st end	
onnection Type:	
nreaded external pipe 1st end	
urst Test Pressure:	
000.0 pounds per square inch	
ayer Composition And Location:	
nd layer braided wire and 1st layer braided wire and outer layer molded rubber,	synthetic
aximum Operating Pressure:	
00.0 pounds per square inch	
nread Size:	
500 inches 1st end	
vdrostatic Test Pressure:	
00.0 pounds per square inch	
side Surface Condition:	
nooth	
easuring Method And Length:	
4.000 inches	
edia For Which Designed:	
iel/oil, hydrocarbon single response	
nread Series Designator:	
ot 1st end	
nelf Life:	
a	
nit Of Measure:	
emilitarization:	
)	

NSN 4720-00-450-6638

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

