NSN 4720-00-450-6642

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-450-6642 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.880 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 1.230 inches **Minimum Inside Bending Radius:** 7.380 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 3200.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided wire and 1st layer braided textile yarn and outer layer rubber impregnated braided cotton cord **Maximum Operating Pressure:** 800.0 pounds per square inch **Thread Size:** 1.000 inches 2nd end Seat Angle: 37.0 degrees 1st end **Inside Surface Condition:** Smooth

Measuring Method And Length:

60.000 inches

Media For Which Designed:

Air and fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

NSN 4720-00-450-6642

Nonmetallic Hose Assembly - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0