

View Online at <https://aerobasegroup.com/nsn/4720-00-450-9367>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.000 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 1.516 inches and 1.609 inches

Minimum Inside Bending Radius:

12.000 inches

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external pipe 1st end

Burst Test Pressure:

8000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber

Maximum Operating Pressure:

2000.0 pounds per square inch

Thread Size:

1.000 inches 1st end

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

4000.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and ozone resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

50.000 inches

Special Features:

Permanently attached fittings

Media For Which Designed:

Fuel/oil, hydrocarbon and hydraulic fluid, water base single response

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0