

NSN 4720-00-451-6033 Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-451-6033 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:**

Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -100.0 degrees fahrenheit single response and 500.0 degrees fahrenheit single response **Outside Diameter:** 0.359 inches **Minimum Inside Bending Radius:** 3.000 inches

Exterior Color:

Natural

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

10000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

28.000 inches

Special Features:

Swaged end fittings

NSN 4720-00-451-6033

Nonmetallic Hose Assembly - Page 2 of 2



Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0