

View Online at <https://aerobasegroup.com/nsn/4720-00-451-6063>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.219 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

Outside Diameter:

0.505 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Natural

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

16000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

11.500 inches working

Special Features:

External support consists of rubber coated non-asbestos fire shield capable of withstanding 2000 degrees f flame for 15 minutes

Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources 80378 have indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Unf 2nd end

Specification Data:

80378-cvc4134-4146 manufacturers specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0