

View Online at <https://aerobasegroup.com/nsn/4720-00-451-7957>

Cross Sectional Shape:

Round

Inside Diameter:

1.000 inches

Tempurature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

1.562 inches

Minimum Inside Bending Radius:

12.000 inches

Angle Between Rigid Elbow Fittings In Deg:

270.0

Flange Outside Diameter:

1.750 inches 1st end

Connection Style:

Plain w/ gasket groove (sae flanged head) 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

8000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally wrapped steel fabric and 2nd layer spirally wrapped steel fabric and 3rd layer braided steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

3000.0 pounds per square inch

Hydrostatic Test Pressure:

4000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

47.750 inches working

Flange Style:

Round w/ out bolt holes 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0