NSN 4720-00-451-9192

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-451-9192

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Minimum Inside Bending Radius:
3.000 inches
End Application:
Grumman a10 aircraft
Connection Style:
Flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Connection Type: Threaded internal tube 1st end
Threaded internal tube 1st end
Threaded internal tube 1st end Thready Qty Per Inch (tpi):
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure:
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 1000.0 pounds per square inch
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location:
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided rayon cord
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided rayon cord Maximum Operating Pressure:
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided rayon cord Maximum Operating Pressure: 250.0 pounds per square inch
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided rayon cord Maximum Operating Pressure: 250.0 pounds per square inch Thread Size:
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided rayon cord Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.500 inches 1st end
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided rayon cord Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle:
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided rayon cord Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 36.0 degrees 1st end
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided rayon cord Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 36.0 degrees 1st end Hydrostatic Test Pressure:
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided rayon cord Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 36.0 degrees 1st end Hydrostatic Test Pressure: 500.0 pounds per square inch
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided rayon cord Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 36.0 degrees 1st end Hydrostatic Test Pressure: 500.0 pounds per square inch Outer Covering Environmental Protection:

Smooth

Inside Surface Condition:

NSN 4720-00-451-9192

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:

39.000 inches excluding end fittings

Special Features:

Weapon system essential

Media For Which Designed:

Air single response

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0