NSN 4720-00-452-2260

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
1.250 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-452-2260

Tempurature Rating:
100.0 degrees fahrenheit single response
Outside Diameter:
Between 2.062 inches and 2.160 inches
Minimum Inside Bending Radius:
7.500 inches
Exterior Color:
Brown or amber
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Fitting Component And Surface Treatment:
Complete fitting dichromate 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
20000.0 pounds per square inch
First End Swivel Action Capability:
Included
Layer Composition And Location:
1st layer spirally laid steel wire
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
1.625 inches 1st end

NSN 4720-00-452-2260

Nonmetallic Hose Assembly - Page 2 of 2



Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Outer Covering Environmental Protection:
Hydraulic solution resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
19.938 inches and 20.000 inches
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0