## NSN 4720-00-454-6178

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches

**Tempurature Rating:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-454-6178

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
20 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
3000.0 pounds per square inch  Flow Angle:
Flow Angle:
Flow Angle: 90.0 degrees 2nd end
Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection:
Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant
Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr:
Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8

## NSN 4720-00-454-6178

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Leng	Λe	easuring	Method	And	Lenath	:
---------------------------	----	----------	--------	-----	--------	---

8.000 inches working

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0