

View Online at <https://aerobasegroup.com/nsn/4720-00-454-7656>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.562 inches

Minimum Inside Bending Radius:

3.000 inches

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal pipe 1st end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

2nd layer woven rayon cord and 1st layer woven rayon cord and outer layer molded rubber, synthetic

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outer Covering Environmental Protection:

Oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0