

View Online at <https://aerobasegroup.com/nsn/4720-00-454-8613>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-67.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

Between 0.469 inches and 0.531 inches

Minimum Inside Bending Radius:

4.500 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

27 2nd end

Burst Test Pressure:

1250.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber, chloroprene and 1st layer braided cotton cord

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Hydrostatic Test Pressure:

625.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and mildew resistant and abrasion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

5.250 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0