

View Online at <https://aerobasegroup.com/nsn/4720-00-454-9567>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.880 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Bolt Circle Diameter:**

1.156 inches 2nd end

**Flange Thickness:**

0.531 inches 2nd end

**Outside Diameter:**

1.230 inches

**Minimum Inside Bending Radius:**

7.375 inches

**Bolt Hole Quantity:**

3 2nd end

**Flange Length:**

2.625 inches 2nd end

**Flange Width:**

2.625 inches 2nd end

**Connection Style:**

Swivel nut flare 1st end

**Bolt Hole Diameter:**

0.344 inches 2nd end

**Raised Face Height:**

0.250 inches 2nd end

**Raised Face Diameter:**

1.625 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

3200.0 pounds per square inch

**Layer Composition And Location:**

2nd layer rubber impregnated braided steel wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord

**Maximum Operating Pressure:**

800.0 pounds per square inch

**Thread Size:**

1.312 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

1600.0 pounds per square inch

**Flow Angle:**

30.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

19.000 inches

**Flange Style:**

Triangular 2nd end

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0